

### Changemate 206

Following the tradition of quality being first, the machine's intensity can compare with the international brands. Various of optional accessories create unlimited possibilities for easy and safe tire services.



#### Highlights

- Standardly equipped with 80mm diameter small cylinder in working table, the clamping force increases 58kg than the 75mm. The rim can be held firmly and assure no rim damage.
- Standardly equipped with spacer, which meets the CE requirement and protects the operator during mounting and demounting.
- The Italian-design pedal assembly has ergonomic structure, sealing performance is stable, appearance updated, unified brand image.
- Double-bending column is made of steel plate with 5mm thickness, high robustness.
- Adopted special parkerising technique cylinder, avoid the cylinder rust, increasing service life.
- Adopted diameter 55mm horizontal shaft, the lengthened hex bar sleeve makes the machine more intensive.
- Optional equipped with AL390 assist arm which adopted tire pressing block for the rim centering, easy and convenient operate. Enhancing the efficiency in mounting and demounting. Optional equipped tire lifter Sr69, labor saving.

#### Technical data

Outside clamping range	11" -24" inch
Inside clamping range	13"-26" inch
Rim width	3"-14" inch
Max wheel diameter	1100 mm
Working pressure	8-10 bar
Bead breaking force	2800 kg
Power supply	110V/220V/380V
Motor Power	0.75Kw/1.1Kw
Rotation per minute	6.5/13rpm
Noise	<70dB
Machine dimensions	1900x1350x2000mm
Packing dimension	1350x1100x1780mm
Net weight	285kg
Gross weight	325kg
Loading in 40 Ft. container	48 sets



#### Optional



A L320 assist arm



AL320H assist arm



Air blasting function