



Tire Changer

Changemate 310

Appearance designed by the former designer of Lamborghini, larger working size, stronger bead breaking force, perfectly meet the customer requirement, with high proficiency.

Highlights

- ▶ The New Z D05 lever less system, easy operation.
- ▶ Z D05 leverless bar device origins from italian patented technology, after many years tested by European market, suitable for each kind of tire mount and demounting.
- ▶ Advance technology of the bead breaker disc movable function which can ensure the bead breaker won't damage the bead by misoperation.
- ▶ Patented technology.
- ▶ Standardly equipped with wheel lifter, labor-saving and maximum lift force can reach to 80kg.
- ▶ Adopted rim centralized positioning which is prevent any damage on the rim, quick and convenient.
- ▶ 200x150mm of the square column got more strength to ensure there is no deformation during mounting and demounting.
- ▶ The diameter of cylinder in right assist arm is 125mm, it is easy to separate the tyre from the rim and it has better performance in mounting and demounting RSC tyres and run-flat tyres.
- ▶ Right assist arm can control movable bead breaker locking synchronously, prevent the machine is damaged by misoperation. Optional equipped CVT motor, low noise, high efficiency.



Technical data

Rim range	13" -30" inch
Rim width	3"-14" inch
Max wheel diameter	200 mm
Working pressure	8-10 bar
Bead breaking force	1000 kg
Power supply	110V/220V/380V
Motor Power	0.8Kw/1.1Kw
Rotation per minute	6.5/13rpm
Noise	<70dB
Machine dimensions	1670x2850x1950mm
Packing dimension	1852x1550x1870mm
Net weight	510kg
Gross weight	605kg
Loading in 40 Ft. container	7 sets

Optional



BAZ00KA-6L



universal Jig



auxiliary Jig for pressing tire