

TCX54 Tire Changer

Professional tilt-column tire changer



*TCX54GP-21U shown with
optional bead press system*

Specifications

Electrical	220V, 1ph, 50-60Hz
Wheel clamping	
External (min-max)	12 - 24 in.
Internal (min-max)	14 - 27 in.
Maximum tire diameter	1100 mm
Maximum rim width	14 in.
Bead loosener width	390 mm
Table rotation speed	7 and 16 rpm clockwise 7 counter-clockwise
Noise level	<70 dB(A)
Operation pressure	8 - 10 bar
Machine weight	275 kg
Dimensions	
Height	1960 mm
Width	1340 mm
Depth	2000 mm

Some dimensions, capacities and specifications may vary depending on tire and wheel configurations.



TCX54GP-21U
with RP11-54PT230
(optional bead press system)

TCX54-21U

Because of continuing technological advancements, specifications, models and options are subject to change without notice.

0917BH

Copyright © 2017, Hunter Engineering Company

Models


- TCX54-21U** Tilt column tire changer
- TCX54GP-21U** Tilt column tire changer with tubeless inflation

Standard equipment

- ✓ Inflation hose and gauge
- ✓ Tire lever with protection
- ✓ Jaw protectors
- ✓ Spare mount head protectors
- ✓ Double-acting shovel cylinder
- ✓ Side shovel protection

Optional equipment

- RP11-54BPS30** Premium bead press system
- RP11-54PT230** Base bead press system
- RP11-5-490223** Side shovel protectors (4)
- RP11-8-11400098** Bead lever protectors (4)
- RP11-8-11400149** Wheel lift



RP11-54PT230 Bead Press System

- ✓ Right side mount
- ✓ Mount head roller and press head
- ✓ Lifting disc



RP11-54BPS30 Bead Press System

- ✓ Left side mount
- ✓ Two disc style mounting rollers with cam
- ✓ Lifting disc

HUNTER
Engineering Company

www.hunter.com

11250 Hunter Drive, Bridgeton, MO 63044, USA
Tel: 1-314-731-3020, Fax: 1-314-731-0132
Email: international@hunter.com

Form 7169-TE-05, 09/17
Supersedes form 7169-TE-05, 06/16